Building a Site Map from Drone Photos

Turning a collection of drone photos into an accurate site map is a task that blends careful flight planning with the right processing tools. The result is a georeferenced, measurable plan that can replace or supplement traditional surveys for many applications. A point cloud viewer is often the final piece that makes the data usable, but the process starts long before the images reach that software.

This guide walks through the main stages, from capture to export, with practical things to watch for at each step. The goal is a map that holds up to measurement and is easy to share with clients or colleagues.

Step 1: Plan the Flight for Map Accuracy

The quality of a site map depends directly on the quality of the source images. You do not need a $50,000 drone, but you do need to fly in a way that gives the processing software enough overlap and consistent lighting.

Set the drone to shoot at a fixed interval, not manually. Most mapping flights use a front overlap of 75-85% and a side overlap of 60-70%. This redundancy lets the software find common points between images, which is how it builds depth and corrects for lens distortion. Fly at a consistent altitude and keep the camera pointed straight down. Even a slight gimbal tilt will introduce errors that are hard to remove later.

Watch for changing light. If clouds move in during the flight, parts of the site will have different exposure levels. The software can balance some of this, but the best maps come from uniform lighting. Fly on a day with thin, even cloud cover if you can.



Step 2: Check Your Ground Control

Accurate site maps need a known reference. Without ground control points (GCPs), your map will be internally consistent but its real-world position and scale will drift. That is fine for a visual overview, but not for measurements or overlays with existing plans.

Place at least three visible targets on the ground before the flight. These can be marked squares, painted crosses, or even large, high-contrast objects whose positions you measure with a GPS rover or a total station. Spread them across the site, not in a straight line. The software will use them to anchor the model to real coordinates.

If you are mapping a small area and do not need survey-grade precision, you can skip GCPs and rely on the drone's built-in GPS, but expect errors of a metre or more. For most construction, drainage, or boundary work, that is not enough.

Step 3: Run the Photogrammetry Pipeline

Back at the desk, you feed the images into photogrammetry software. The software looks for matching features across overlapping images and uses those matches to calculate the position of each camera at the moment of capture. This is called bundle adjustment, and it produces a sparse point cloud: a set of 3D points that represent the surface.

From that point cloud, the software can generate a dense point cloud, an orthomosaic (a single, geometrically corrected image of the whole site), and a digital surface model (DSM) that shows the height of every object: trees, buildings, ground.

What to watch for here: processing time scales with image count and resolution. A site with 300 images at 20 megapixels each can take several hours. Most software shows you a quality report after processing. Check the tie-point density and the reprojection error. If the error is more than a few pixels, the alignment is weak. You may need to add manual tie points or fly again with more overlap.

National Drone Services provides a platform for uploading and processing drone data that handles this entire pipeline. That kind of service is especially useful when you have many sites to process and want a consistent workflow without installing software on every machine.

Step 4: Refine the Point Cloud

The raw point cloud from photogrammetry will include points on the ground, on buildings, and on vegetation. For a site map, you usually want only the ground surface. Vegetation points create a bumpy, inaccurate model.



Use the classification tools in your point cloud viewer or processing software to filter out points above a certain height or with a certain colour signature. Some tools let you manually paint areas to remove or keep. This step is tedious but crucial. A site map with tree canopy showing as ground elevation will be wrong by metres in places.

If your software supports it, run a ground classification algorithm that uses colour and height variation to guess which points are ground and which are not. Always check the result visually before exporting.

Step 5: Generate the Site Map

With the cleaned point cloud, you can produce the final deliverables. A typical site map set includes:

- An orthomosaic: a top-down image with every pixel in its real-world position. You can measure distances and areas directly on it.
- A contour map: lines of equal elevation overlaid on the ortho. Contour intervals of 0.5 m or 1 m work for most sites.
- A digital terrain model (DTM): the bare-earth surface without vegetation or structures. This is the file you would use for volume calculations or drainage design.


Export each of these in a standard GIS format such as GeoTIFF or Shapefile. Your client or engineer will thank you for not sending proprietary formats.

Step 6: Share and Review in a Point Cloud Viewer

Before handing over the final files, review the map in a point cloud viewer. This is where you catch errors that look fine in a flat image. A viewer lets you rotate, measure, and toggle layers. You can check whether the contours actually follow the ground and whether the ortho aligns with the GCPs.

Some viewers also support annotations, markups, and comparison between surveys. If you map the same site months later, you can overlay the two point clouds and see exactly where material was added or removed. That is valuable for stockpile management, cut-and-fill tracking, or monitoring erosion.

A good point cloud viewer runs in a browser, so you can share a link with stakeholders without sending huge files. The viewer handles the heavy rendering on its end. The person on the other side does not need special software or a powerful computer.



Common Pitfalls and How to Avoid Them

Even with careful planning, things go wrong. Here are the most frequent issues and what to do about them:

- **Blurry images** from flying too fast or too low. Keep shutter speed above 1/1000 s and fly at a steady speed. Slow down if the light is low.
- **Gaps in coverage** from insufficient overlap. Check the flight log after each run. Most drone apps will warn you if coverage is thin.
- **GPS drift** on the drone. If the drone's position jumps during flight, the images may not align. Fly in open sky away from tall structures that reflect GPS signals.
- **Vegetation movement** between passes. Trees and tall grass move in the wind. The software cannot match moving features. Fly on a calm day or accept that vegetated areas will be noisy.
- **Incorrect coordinate system** in the export. Always set the output CRS to match the local mapping standard. A map in WGS84 will not overlay correctly on a local grid.

Fixing these issues before processing saves hours of rework. A short pre-flight checklist that includes wind speed, GPS health, and camera settings is worth the time.

The process from raw photos to a finished site map is not automatic, but it is repeatable. With good flight planning, proper ground control, and a solid processing workflow, you can produce maps that stand up to measurement and meet professional standards. Services such as National Drone Services make the processing and sharing part easier, but the quality still depends on the capture. Get that right and the rest follows.

National Drone Services on social media Facebook